

DELABIE

90
1928
2018
DELABIE



COMFORT
WATER SAVINGS
VANDAL-RESISTANT
SAFETY



TEMPOMIX

Time flow basin mixer

- ▶ Soft-touch operation
- ▶ Time flow 7 seconds
- ▶ Flow rate 3 lpm at 3 bar
- ▶ Solid brass body and reinforced fixings
- ▶ Maximum temperature limiter

10
YEAR
WARRANTY

More information at delabie.co.uk



Faucets

Tel: (01495) 767600 Fax: (01495) 767601 Email: sales@faucets.co.uk

Prices are excluding VAT

Commercial controls - Basins




TEMPOMATIC 4

Electronic mixer or tap with integrated 6V Lithium batteries, reduced-stagnation solenoid valve and electronic unit.

- Flow rate pre-set at 3 lpm at 3 bar
- PEX flexibles with filters and non-return valves
- Chrome-plated solid brass body with reinforced fixings
- Anti-blocking security and temperature limiter
- Duty flush (~60 seconds every 24 hours after last use)

Stocked*

Deck-mtd mixer Ø 15mm	49000615	£341.28
Deck-mtd tap Ø 15mm	44000615*	£307.84
Wall-mtd tap L. 125 F3/4"	443406	£298.87
Wall-mtd tap L. 190 F3/4"	443506	£332.32



BINOPTIC

Electronic mixer or tap with infrared presence detection.

- Flow rate pre-set at 3 lpm at 3 bar
- PEX flexibles with filters and Ø 15mm solenoid valves
- Chrome-plated brass body with reinforced fixings
- Anti-blocking security and temperature limiter
- Duty flush (~60 seconds every 24 hours after the last use)
- Independent IP65 electronic control unit and shock-resistant sensor

Deck-mtd mixer	378MCH15	£441.04
Deck-mtd tap	37801515	£332.22
Wall-mtd tap	379DER15	£339.90
Recessed tap	379ENC15	£348.73



TEMPOMIX 3

Time flow mixer with soft-touch operation and temperature control via the push-button.

- Time flow pre-set at 7 seconds (can be adjusted from 3 - 10 seconds)
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6lpm
- PEX flexibles with filters, non-return valves and stopcocks
- Chrome-plated solid brass body with reinforced fixings
- Tamperproof, scale-resistant flow straightener

Ø 15mm	79400015	£242.44
F3/4"	794000	£235.65




TEMPOSOFT MIX 2

Deck-mounted time flow mixer with soft-touch operation.

- Soft-touch operation
- Time flow ~7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Chrome-plated solid brass body with reinforced fixings
- Side temperature control and temperature limiter

Ø 15mm	74250015	£158.07
--------	----------	---------



TEMPOSOFT 2 tap

Deck-mounted time flow tap with soft-touch operation.

- Soft-touch operation
- Time flow ~7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Chrome-plated solid brass body

Stocked*

M1/2"	740500*	£87.36
-------	---------	--------




TEMPOSOFT 2 wall-mounted

Wall-mounted time flow tap with soft-touch operation.

- Soft-touch operation
- Time flow ~7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Chrome-plated solid brass body M1/2"

L. 110mm	741500	£66.14
L. 150mm	741550	£79.68




TEMPOMIX

Deck-mounted time flow basin mixer with soft-touch operation.

- Soft-touch operation
- Temperature control and operation via the push-button
- Time flow 7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Chrome-plated solid brass body
- Maximum temperature limiter

Ø 15mm	79500015*	£212.73
--------	-----------	---------



TEMPOSTOP

Deck-mounted time flow tap.

- Time flow ~7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Chrome-plated solid brass body with spout H. 35mm, L. 110mm
- Tamperproof, scale-resistant flow straightener

Stocked*

15mm	745250*	£68.13
M1/2", reinf. fixing	745300	£69.56
M1/2", anti-blocking	745301	£73.08
15mm, anti-blocking	745351*	£80.05
15mm lever-op	745450	£91.28



Commercial controls - Showers

**SECURITHERM electronic**

Aluminium powder-coated thermostatic battery-operated shower panel for wall-mounted installation.

- SECURITHERM thermostatic mixer
- 6V Battery-operated infrared sensor
- Anti-scalding hot water safety
- Pre-set maximum temperature limiter
- Shuts off voluntarily or automatically after ~60 seconds
- Tamperproof ROUND shower head with scale-resistant nozzle, 6 lpm at 3 bar
- Integrated stopcocks, filters and non-return valves
- Thermal shocks are possible

With top inlets Ø 15mm **79240015** **£833.62**

**SECURITHERM time flow**

Aluminium powder-coated shower panel for wall-mounted installation.

- SECURITHERM thermostatic mixer
- Time flow ~30 seconds
- Soft-touch operation
- Anti-scalding hot water safety
- Pre-set maximum temperature limiter
- Tamperproof ROUND shower head with scale-resistant nozzle, 6 lpm at 3 bar
- Integrated stopcocks, filters and non-return valves
- Thermal shocks are possible

With top inlets Ø 15mm **79230015** **£680.20**

**TEMPOMIX time flow**

Aluminium powder-coated shower panel for wall-mounted installation.

- TEMPOMIX time flow mixer
- Time flow ~30 seconds
- Soft-touch operation
- Tamperproof ROUND shower head with scale-resistant nozzle, 6 lpm at 3 bar
- Ø 15mm connections with integrated stopcocks, filters and non-return valves

With top inlets **79030015** **£577.90**

**SPORTING 2 shower panel**

Anodised aluminium shower panel with adjustable connector for top or back inlets.

- Time flow ~30 seconds
- Soft-touch operation
- Tamperproof fixed shower head with scale-resistant nozzle, 6 lpm at 3 bar
- Integrated stopcock, filter and non-return valve
- M $\frac{1}{2}$ " connection for mixed water supply

Stocked*


With top/back inlet **714700*** **£195.67**

**TEMPOMIX 3**

Time flow shower kit in a waterproof recessing housing.

- Time flow ~30 seconds with soft-touch operation
- Tamperproof ROUND shower head with scale-resistant nozzle
- Flow rate 6 lpm at 3 bar
- Chrome-plated metal wall plate 160 × 160mm
- Waterproof housing for all installation types

Shower kit with top inlet	794BOX1 + 794219	£205.55 £246.26
Shower mixer with top inlet	794BOX1 + 794218	£205.55 £193.04
Shower kit with bottom inlet	794BOX2 + 794219	£205.55 £246.26
Shower mixer with bottom inlet	794BOX2 + 794218	£205.55 £193.04

**TEMPOSTOP**

Cross wall time flow shower kit.

- Time flow ~15 or 30 seconds
- Vandal resistant cross wall control
- Tamperproof ROUND shower head with scale-resistant nozzle
- Flow rate 6 lpm at 3 bar
- Chrome-plated solid brass body
- Concealed fixings and anti-rotating nut

For walls ≤ 150mm	749159	£230.41
For walls ≤ 200mm, AB	747214	£223.78

**TEMPOGENOU**

Knee-operated time flow valve for hands-free operation.

- Time flow ~7 seconds and pre-set flow rate 3 lpm
- Control lever reinforced by stainless steel rod
- Wall plate mounted via 4 stainless steel screws
- Cold or mixed water supply

MM $\frac{1}{2}$ ", inline	73544715	£119.80
MM $\frac{1}{2}$ ", angled	734100	£94.22

**Deck-mounted spout**

Fixed cast brass spout for hands-free operation.

- Spout L. 140mm, H. 120mm, M $\frac{1}{2}$ "
- Reinforced fixing by 3 stainless steel screws
- Chrome-plated solid brass
- Flow straightener regulated at 3 lpm

Deck-mounted	981142	£77.39
--------------	---------------	---------------



Tel: (01495) 767600 Fax: (01495) 767601 Email: sales@faucets.co.uk

Prices are excluding VAT

Commercial controls - WCs



TEMPOMATIC WC

Cross wall electronic direct flush valve for WCs.

- IP65 independent electronic unit
- Mains supply with 1" solenoid valve
- Voluntary activation or automatic flush
- Time flow ~7 seconds, can be adjusted from 3-12 seconds
- Detection distance, flow rate and flush volume can be adjusted
- Stopcock, connection washer and vacuum breaker

For walls ≤ 30mm	463030	£755.68
For walls ≤ 160mm	463150	£755.68
For walls ≤ 225mm	463200	£761.50



TEMPOMATIC dual control WC

Electronic direct flush valve in a waterproof housing.

- Satin finish stainless steel wall plate 186 × 186mm
- Voluntary flush via push-button (anti-blocking function) or automatically when user leaves
- Intelligent flush volume adapts according to use
- Waterproof housing for all installation types
- F³/₄" flush valve
- Integrated vacuum breaker, stopcock and flow rate/flush volume adjuster

6V battery	464PBOX	£133.67
	+ 464006	£423.30
Mains	464SBOX	£133.67
	+ 464000	£445.58




TEMPOFLUX 3 WC

Time flow direct flush valve in a waterproof housing.

- Satin finish stainless steel wall plate 210 × 162mm
- Dual flush 3L/6L, can be adjusted to 2L/4L
- Compatible with wall finishes 10-120mm
- Waterproof housing for all installation types
- F³/₄" flush valve is compatible with sea water and grey water
- Integrated vacuum breaker, stopcock and flow rate/flush volume adjuster

3L/6L recessed	763BOX	£111.39
	+ 763000	£133.67



TEMPOFLUX 1 WC cross wall kit

Cross wall time flow flush kit.

- Cross wall control, can be cut to size
- Soft-touch operation
- Inlet M³/₄" with integrated stopcock and flow rate/flush volume adjuster
- Integrated vacuum breaker
- Connection washer Ø 32/55mm

≤ 150mm, with flush tube	761700	£212.36
≤ 200mm, without flush tube	761200	£181.78

Commercial controls - Urinals



TEMPOMATIC 4 urinal exposed

Electronic valve with integrated 6V Lithium battery, reduced-stagnation solenoid valve and electronic unit.

- High frequency mode, active during busy periods
- 3 rinsing programmes
- Hygienic duty flush every 24 hours after last use
- Integrated stopcock and flow rate 0.25 l/sec at 3 bar, can be adjusted
- One-piece chrome-plated metal body M¹/₂"

Inline	479406	£335.30
Angled	479408	£299.37
Angled, flush tube Ø 35mm	479407	£323.33



TEMPOMATIC 4 urinal recessed

Electronic valve for waterproof, recessed individual urinals.

- Mains supply or battery operated
- Stainless steel wall plate 145 × 145mm with integrated electronics
- High frequency mode
- 3 rinsing programmes
- Hygienic duty flush every 12 or 24 hours (or off)
- Waterproof housing, for all installation types

Note: other finishes also available

Polished st. steel 6V battery	430PBOX	£108.19
	+ 430016	£317.68
Polished st. steel Mains	430SBOX	£109.35
	+ 430010	£339.55




TEMPOFLUX urinal recessed

Time flow urinal valve in a waterproof housing.

- Satin finish stainless steel wall plate 145 × 145mm
- Flow rate 0.15 l/sec at 3 bar, can be adjusted
- Time flow 3 seconds with soft-touch operation
- Compatible with wall finishes 10 - 120mm
- Waterproof housing for all installation types
- F³/₄" flush valve is compatible with sea water and grey water
- Integrated stopcock and flow rate adjuster

Satin stainless steel	778BOX	£102.89
	+ 778700	£150.38



TEMPOSOFT 2 urinal exposed

Exposed time flow urinal valve with soft-touch operation for standard or siphon action urinals.

- Soft-touch operation
- Time flow ~3 seconds
- Flow rate pre-set at 0.15 l/sec at 3 bar, can be adjusted
- Chrome-plated solid brass body M¹/₂"

Inline	777800	£66.07
Angled	778800	£61.08



Frame systems



TEMPOFIX 3 with TEMPOMATIC 4 urinal

Frame system W. 430mm with electronic urinal valve.

- Adjustable frame system in black powder-coated steel
- Delivered pre-mounted for quick installation
- Fixes to floor and load-bearing walls
- Bracket can be adjusted
- For walls up to 120mm
- Features TEMPOMATIC 4 electronic valve F½"
- 230/6V mains supply
- For urinal valves Ø 35mm

Battery-operated versions also available

Bright stainless steel finish	543000 + 430010	£379.84 £339.55
Satin stainless steel finish	543000 + 430000	£379.84 £339.55



TEMPOFIX 3 with TEMPOFLUX urinal

Frame system W. 430mm with time flow urinal valve.

- Adjustable frame system in black powder-coated steel
- Delivered pre-mounted for quick installation
- Fixes to floor and load-bearing walls
- Bracket height can be adjusted
- Features TEMPOFLUX F½" time flow flush valve
- Time flow ~3 seconds

For urinals Ø 35mm	543006 + 778700	£368.33 £150.38
For urinals with flexible ½"	543006D + 778700	£368.33 £150.38



TEMPOFIX 3 with TEMPOMATIC dual control WC

Frame system W. 350mm with electronic WC valve.

- Adjustable frame system in black powder-coated steel
- Delivered pre-mounted for quick installation
- Fixes to floor and load-bearing walls up to 120mm thick
- Soil pipe with Ø 110mm connection washer
- Complies with French standard NF D12-208
- Features TEMPOMATIC dual control direct flush valve F¾"

Battery-operated versions also available

Self-supporting model, mains	564005DE + 464000	£356.46 £445.58
Wall-mounted model, mains	564000DE + 464000	£339.75 £445.58



TEMPOFIX 3 with TEMPOFLUX 3 AB

Frame system W. 350mm with time flow WC valve.

- Adjustable frame system in black powder-coated steel
- Delivered pre-mounted for quick installation
- Fixes to floor and load-bearing walls up to 120mm thick
- Soil pipe with Ø 110mm connection washer
- Complies with French standard NF D12-208
- Features TEMPOFLUX 3 F¾" time flow direct flush valve

Self-supporting model, 6V	564065DE + 763000	£356.46 £133.67
Self-supporting model, mains	564060DE + 763000	£339.75 £133.67

Additional Fittings



PREMIX NANO

TMV3 approved point-of-use thermostatic mixing valve.

- Anti-scalding safety: immediate shut-off if cold or hot water supply fails
- Temperature pre-set at 38°C, can be adjusted from 34 - 60°C
- Thermal shocks are possible
- Integrated filters and non-return valves
- For 1 - 2 taps or 1 shower

Stocked*

M½" 15mm, chrome	732116*	£81.62
M½" 15mm, nickel	732115	£69.36



PREMIX COMFORT

Group thermostatic mixing valve for mixed water distribution.

- Anti-scalding safety: maximum temperature limiter
- Temperature pre-set at 38°C, can be adjusted from 32 - 42°C
- Thermal shocks are possible
- Integrated filters and non-return valves can be accessed externally
- For up to 40 points-of-use, flow rate 55 - 190 lpm at 3 bar

¾", 55 lpm	731002	£467.31
1", 90 lpm	731003	£724.33
1¼", 140 lpm	731004	£1,039.76
1½", 190 lpm	731005	£1,343.52



Adjustable height floor trap

Floor trap for soft or vinyl floors with adjustable height.

- Flow rate 36 lpm, outlet Ø 43mm
- Water level 50mm
- Bright polished stainless steel grid Ø 114mm
- Integrated plate to seal waterproof membrane
- Height adjusts up to 85mm with extension

Stocked*

Outlet Ø 43 mm	683002UK*	£57.46
----------------	-----------	---------------



BIOSAFE spout outlet

Hygienic spout outlet for mixers and taps.

- Free flow outlet with no grid or partitions in contact with the water
- Water cannot stagnate in the internal parts
- Scale-resistant Hostaform® interior
- Chrome-plated brass collar
- Flow rate must be limited to ensure a smooth, laminar flow

M24/100	923024	£6.00
F22/100	923022	£6.00



Hospital




TEMPOMATIC MIX hospital mixer

Electronic mixer with swivelling spout. Smooth body and spout interiors.

- Infrared sensor and temperature control via control lever L. 100mm
- Mains supply 230/12V or 6V Lithium battery-operated
- Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Duty flush (~60 seconds every 24 hours after last use)

H. 165 L. 160	20164T115	£546.73
H. 305 L. 250	20164T415	£587.01
H. 165 L. 160, 6V	20464T115	£719.37
H. 305 L. 250, 6V	20464T415	£742.40



TEMPOMATIC MIX BIOCLIP hospital mixer

Electronic mixer with BIOCLIP removable spout. Smooth body and spout interiors.

- BIOCLIP spout can be removed for cleaning and disinfection
- Infrared sensor and temperature control via control lever L. 100mm
- Mains supply 230/12V
- Flow rate limited to 7 lpm at 3 bar
- Duty flush (~60 seconds every 24 hours after last use)
- Suitable for BIOFIL spout filters

Spout H. 160	20870T115	£615.79
Spout H. 300	20870T315	£638.80



Mechanical mixer BIOCLIP spout

Mixer with BIOCLIP removable spout and Hygiene lever. Smooth body and spout interiors.

- BIOCLIP spout can be removed for cleaning and disinfection
- Ceramic cartridge Ø 40mm with maximum temperature limiter
- Flow rate limited to 5 lpm at 3 bar
- Suitable for BIOFIL spout filters

Spout H. 160	2870T1	£300.06
Spout H. 300	2870T3	£323.77




BIOSAFE mechanical mixer

Mixer with no spout and very low water volume in the body.

- BIOSAFE hygienic spout outlet integrated into the body
- Smooth interior and very low water volume
- Flow rate limited to 4 lpm at 3 bar
- Thermal shocks are possible
- Available with Pressure Balancing (EP)
- Copper tails

With waste	26206	£211.65
No waste	26216	£189.37
EP, with waste	26206EP	£245.07
EP, no waste	26216EP	£222.79




SECURITHERM sequential mixer

Sequential thermostatic mixer.

- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- No non-return valves on the inlets
- Smooth interior slows bacterial development

15mm, lever L. 146	H960015	£303.69
15mm, lever L. 100	H960015L	£300.74
Coppertails, lever L. 146	H9600610	£329.41
Coppertails, lever L. 100	H9600610L	£332.42



SECURITHERM BIOCLIP sequential mixer

Removable sequential thermostatic BIOCLIP mixer.

- Mixer can be easily removed for cleaning and disinfection
- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- No non-return valves on the inlets
- Smooth interior slows bacterial development

Stocked*		
15mm, lever L. 146	H960515	£350.41
15mm, lever L. 100	H960515L	£347.00
Coppertails, lever L. 146	H9605610*	£389.66
Coppertails, lever L. 100	H9605610L	£383.29



Wall-mtd SECURITHERM BIOCLIP mixer

Sequential thermostatic mixer with BIOCLIP spout.

- BIOCLIP spout can be removed for cleaning and disinfection
- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- No non-return valves on the inlets
- Smooth interior slows bacterial development

Stocked*		
150mm, inline SP	H9611P	£432.21
200mm, inline SP	H9614P*	£431.42



Pillar-mtd SECURITHERM BIOCLIP mixer

Sequential thermostatic mixer with BIOCLIP spout.

- BIOCLIP spout can be removed for cleaning and disinfection
- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- No non-return valves on the inlets
- Smooth interior slows bacterial development

200mm, pillar	H9615	£491.64
---------------	--------------	----------------



Hospital

**BIOFIL cartridge filter**

Single use BIOFIL cartridge with integrated filter.

- Immediate protection against waterborne nosocomial infection
- Sterilising grade 0.1 micron absolute-rated
- Maximum lifespan 62 days for both non-sterile and sterile filter
- 10 cartridges individually wrapped

Sterile	20050A.10P	£708.43
Sterile	20050P.10P	£708.43
Non-sterile	30050A.10P	£565.60
Non-sterile	30050P.10P	£565.60
Connector 'A' F22/100	820022	£22.28
Connector 'A' M24/100	820024	£22.28
Connector 'P' F22/100	820122	£27.85
Connector 'P' M24/100	820124	£27.85

**BIOFIL shower head filter**

Single use BIOFIL shower head with integrated filter.

- Immediate protection against waterborne nosocomial infection
- Sterilising grade 0.1 micron absolute-rated
- Maximum lifespan 62 days for both non-sterile and sterile filter
- 10 shower heads individually wrapped

Sterile threaded	20061.10P	£889.22
Non-sterile threaded	30061.10P	£746.10
Sterile push-fit	20060.10P	£889.22
Non-sterile push-fit	30060.10P	£746.10

**BIOFIL spout filter**

Single use BIOFIL spout head with integrated filter.

- Immediate protection against waterborne nosocomial infection
- Sterilising grade 0.1 micron absolute-rated
- Maximum lifespan 62 days for both non-sterile and sterile filter
- 10 spouts individually wrapped

Sterile	20040.10P	£732.86
Non-sterile	30040.10P	£722.02

**BIOCLIP spouts**

Removable BIOCLIP spouts in stainless steel and Hostaform®.

- For use with BIOCLIP mixers/taps
- Removable stainless steel spouts Ø 28mm with hygienic flow straightener suitable for BIOFIL terminal filters. Available in two lengths, 129mm and 77mm
- Disposable Hostaform® spouts Ø 22mm with star-shaped flow straightener. Length 125mm. Individually wrapped

2 x St. steel, L. 129	20002	£75.49
2 x St. steel, L. 77	20003	£67.71
15 x Hostaform®, L. 125	20015	£75.04

**SECURITHERM Securitouch sequential shower**

Sequential thermostatic shower mixer.

- Progressive temperature control from cold water to 39°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Thermostatic sequential cartridge Ø 40mm with maximum temperature limiter
- Smooth interior slows bacterial development
- Flow rate regulated at 9 lpm
- Supplied with in-line STOP/CHECK connectors

M½" bottom outlet	H963015	£291.64
M¾" top outlet	H964015	£291.64

**SECURITHERM Securitouch shower**

Dual control thermostatic shower mixer.

- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Securitouch thermal insulation prevents burns
- Adjustable temperature 25 - 41°C with maximum temperature limiter
- M½" shower outlet
- 150mm in-line connectors with filters and non-return valves
- Supplied with in-line STOP/CHECK connectors

M½"	H9741TP	£263.82
-----	---------	---------

**SECURITHERM sequential recessed shower**

Sequential thermostatic shower mixer in a waterproof housing.

- Sequential shower mixer with polished stainless steel cover plate
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Securitouch thermal insulation prevents burns
- Maximum temperature limiter
- Flow rate regulated at 9 lpm
- Waterproof recessing housing

Stocked*

SECURITHERM shower	H9632*	£289.40
Waterproof housing	790BOX*	£81.60

**SECURITHERM EP Securitouch shower**

Pressure-balancing shower mixer.

- Securitouch thermal insulation prevents burns
- EP pressure-balancing ceramic cartridge Ø 40mm with maximum temperature limiter
- M½" shower outlet with flow rate regulated at 9 lpm
- M½" M¾" offset connectors with filters and non-return valves

With STOP/PURGE unions	2739EP	£265.71
------------------------	--------	---------



Accessibility & Independence



DOC M recessed shower pack

DOC M compliant white powder-coated shower pack.

- 2 × drop-down rails, 3 × 600mm grab bars, 2 × 450mm grab bars
- Lift-up shower seat with backrest
- 2 × white PVC shower curtain and rail
- SECURITHERM thermostatic recessed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and wall outlet
- Stainless steel coat hook

White powder-coated	DOC M REC1	£1,676.56
---------------------	------------	-----------



DOC M recessed shower pack

DOC M compliant blue powder-coated shower pack.

- 2 × drop-down rails, 3 × 600mm grab bars, 2 × 450mm grab bars
- Lift-up shower seat with backrest
- 2 × white PVC shower curtain and rail
- SECURITHERM thermostatic recessed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and wall outlet
- Stainless steel coat hook

Blue powder-coated	DOC M REC2	£1,676.56
--------------------	------------	-----------



DOC M exposed shower pack

DOC M compliant white powder-coated shower pack.

- 2 × drop-down rails, 3 × 600mm grab bars, 2 × 450mm grab bars
- Lift-up shower seat with backrest
- 2 × white PVC shower curtain and rail
- SECURITHERM thermostatic exposed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and 1.0m riser pipe
- Stainless steel coat hook

White powder-coated	DOC M EXP1	£1,510.71
---------------------	------------	-----------



DOC M exposed shower pack

DOC M compliant blue powder-coated shower pack.

- 2 × drop-down rails, 3 × 600mm grab bars, 2 × 450mm grab bars
- Lift-up shower seat with backrest
- 2 × white PVC shower curtain and rail
- SECURITHERM thermostatic exposed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and 1.0m riser pipe
- Stainless steel coat hook

Blue powder-coated	DOC M EXP2	£1,510.71
--------------------	------------	-----------

Accessibility & Independence



Toilet paper dispenser

Large paper dispenser.

- One-piece hinged cover for easy maintenance and better hygiene
- With lock and standard DELABIE key
- With back piece: protects the paper from wall imperfections, damp and dust
- Level control
- Model for 400m rolls
- Dimensions: Ø 305mm, depth 135mm

Bright polished st steel	2911	£132.19
Polished satin st steel	2912	£132.19
White lacquered steel	2910	£72.54



HIGHFLOW hand dryer

Compact air pulse hand dryer.

- Robust model
- High speed: dries in 10 - 12 seconds
- Choice of warm or cold air
- Anti-blocking
- Bacteriostatic 304 stainless steel; 1mm thick
- Dimensions: 175 × 238 × 267mm
- 3-year warranty. CE marked

Bright polished st steel	510622	£387.81
Polished satin st steel	510622S	£387.81

Hygienic Accessories



Electronic soap dispenser

Wall-mounted stainless steel liquid soap dispenser.

- Non-touch, no waste pump dispenser, 0.8ml. dose
- Power supply: 6 AA batteries included
- Window allows soap level to be checked
- Capacity: 0.65 litres
- For vegetable-based liquid soap (up to 3,000 mPa.s)

Electronic	510587	£122.80
------------	--------	---------



Liquid soap dispenser

Liquid soap dispenser with soft-touch operation.

- 304 Stainless steel
- One-piece hinged cover for easy maintenance and better hygiene
- Anti-blocking system and no-waste pump dispenser
- With lock and standard DELABIE key
- Level control
- For vegetable-based liquid soap (up to 3,000 mPa.s)

1L, bright polished	510580	£91.85
1L, polished satin	510582	£86.00
1L, white epoxy	510581	£74.96
0.5L, bright polished	510583	£86.34
0.5L, polished satin	510586	£80.85
0.5L, white epoxy	510584	£70.44



Sanitary Ware

**BOB washbasin**

Wall-mounted stainless steel washbasin with concealed drainage.

- Basin internal diameter 310mm
- Bacteriostatic 304 stainless steel, 1.2mm thick
- Polished satin finish
- Rounded edges prevent injury
- Vandal-resistant shrouded basin, concealed trap
- Supplied with 1½" waste and trap, no overflow
- Complies with EN 14688

Without tap hole	120130	£282.83
------------------	---------------	----------------

**FRAJU washbasin**

Wall-mounted stainless steel washbasin.

- Overall size 540 × 480mm
- Bacteriostatic 304 stainless steel, 1.2mm for bowl, 1.5mm for surround
- Polished satin finish
- Rounded edges prevent injury
- Supplied with 1¼" waste, no overflow
- Complies with EN 14688

Without tap hole	120430	£297.68
Tap hole Ø 35mm	121430	£297.68

**CANAL wash trough**

Wall-mounted stainless steel wash trough for 1 - 5 services.

- Bacteriostatic 304 stainless steel, 1mm for bowl, 1.5mm for surround
- Polished satin finish
- Light weight, easy to install (no joint concealers)
- Supplied with brackets and fixing elements
- Complies with EN 14296

L. 600, 1 service	120240	£332.07
L. 1,200, 2 services	120250	£403.31
L. 1,200, with tap hole	121250	£403.31
L. 1,400, 2-3 services	120260	£434.75
L. 1,800, 3-4 services	120280	£498.64
L. 2,400, 4 services	120300	£571.97
L. 3,000, 5 services	120310	£630.64

**SD drinking fountain**

Wall-mounted stainless steel drinking fountain.

- Bacteriostatic 304 stainless steel, 1.5mm thick
- Polished satin finish
- Rounded edges prevent injury
- Supplied with WRAS approved chrome-plated time flow bubbler tap, M¾"
- Vandal-resistant, flat perforated waste, outlet 1¼"
- Weight 2.4kg.
- Supplied with fixing elements

With bubbler	180800	£337.14
--------------	---------------	----------------

**S21 and 700 WC pans**

Wall-hung or floor-standing stainless steel WC pans.

- Bacteriostatic 304 stainless steel, 1.5mm thick
- Polished satin finish
- One-piece pressed bowl with no seams
- Concealed perimetral flushing rim
- Horizontal inlet Ø 55mm; horizontal waste Ø 100mm. Supplied with PVC pipe
- Easy to install

S21 S wall-hung	110310	£715.20
S21 P floor-mtd	110300	£711.95
700 S wall-hung	110710	£915.83
700 P floor-mtd	110700	£783.13

**Trough urinal**

Wall-hung stainless steel trough urinal

- Bacteriostatic 304 stainless steel, 1.2mm thick
- Polished satin finish
- Top inlet M½" and sparge pipe for rinsing
- 1½" waste outlet, drains on the right side
- Weight: 1,200mm model is 17.5kg, 1,800mm model is 24.8kg, 2,400mm model is 32.1kg
- Siphon not included

L. 1,200mm	130100	£589.75
L. 1,800mm	130110	£791.47
L. 2,400mm	130120	£1,049.26

**MINERALCAST wash trough**

Wall-mounted wash trough available with 2 or 3 services.

- Natural minerals and polyester resin composite
- Uniform, non-porous surface
- One-piece cast washbasin with no seams
- Central tap hole Ø 35mm
- Supplied with 1½" waste, no overflow

L. 1,200mm, 2 services	454122	£1,016.14
L. 1,800mm, 3 services	454182	£1,314.70

**MINERALCAST wash trough**

Wall-mounted wash trough with 3 services.

- Natural minerals and polyester resin composite
- Uniform, non-porous surface, ideal for schools
- One-piece cast washbasin with no seams
- With incline to prevent pooling
- Supplied with three 1¼" wastes, no overflow

L. 1,400mm, 3 services	453140	£1,403.73
------------------------	---------------	------------------

Safety Controls



Free-standing eye wash and shower combination

Free-standing safety eye wash and shower with large flow rates.

- Frost-free system as standard
- 304 stainless steel basin Ø 250mm, flow rate 20 lpm at 3 bar
- Eye wash spray heads fitted with auto-ejecting protective caps
- Circular shower head Ø 250mm, flow rate 70 lpm at 1 bar (120 lpm at 3 bar)
- Water supply F1"
- Galvanised steel pipes, green powder-coated controls

Combination	9203	£830.40
-------------	------	---------



Wall-mounted safety shower

Wall-mounted recessed safety shower with manual control.

- Frost-free system as standard
- Circular shower head Ø 250mm, flow rate 70 lpm at 1 bar (120 lpm at 3 bar)
- ¼-turn valve, flow activated by triangular handle
- Water supply F1"
- Galvanised steel pipes, green powder-coated shower head and handle

Shower	9108	£171.12
--------	------	---------




Wall-mounted eye wash station

Wall-mounted eye wash station with manual control.

- Frost-free system as standard
- 304 stainless steel basin Ø 250mm, flow rate 20 lpm at 3 bar
- Eye wash spray heads fitted with auto-ejecting protective caps
- ¼-turn valve, flow activated by hand control
- Water supply M½"
- Galvanised steel pipes, green powder-coated bowl and control

Wall-mounted	9102	£348.91
--------------	------	---------



Free-standing eye wash station

Free-standing eye wash station with manual and pedal controls.

- Frost-free system as standard
- 304 stainless steel basin Ø 250mm, flow rate 20 lpm at 3 bar
- Eye wash spray heads fitted with auto-ejecting protective caps
- ¼-turn valve, flow activated by hand or pedal controls
- Water supply F1"
- Galvanised steel pipes, green powder-coated bowl and controls

Free-standing	9201	£565.26
---------------	------	---------




Single spray eye wash

Trigger-operated single spray eye wash.

- Eye wash spray head fitted with auto-ejecting protective cap
- Trigger-operated, spring automatically shuts-off spray
- Flow rate 6 lpm at 3 bar
- Integrated aerator with stainless steel double filter
- Ergonomic grip and trigger in green polypropylene

Wall-mounted	9120C	£139.59
Deck-mounted	9140C	£182.83



Dual spray eye wash

Trigger-operated dual spray eye wash.

- Eye wash spray heads fitted with auto-ejecting protective caps
- Trigger-operated, spring automatically shuts-off spray
- Flow rate 6 lpm at 3 bar
- Integrated aerator with stainless steel double filter
- Ergonomic grip and trigger in green polypropylene

Wall-mounted	9121	£153.50
Deck-mounted	9141	£209.16



Safety shower head

Replacement shower head for safety shower.

- Circular shower head Ø 250mm, M1"
- Green shock-resistant ABS
- Flow rate 70 lpm at 1 bar (120 lpm at 3 bar)
- Water supply F1"

Shower head	9225	£48.14
-------------	------	--------



Aerator & protective caps

Replacement aerators and protective caps for eye wash stations.

- Aerator F22/100 with grid for comfortable spray
- Protective caps in green, shock-resistant ABS. Eject automatically when eye wash is activated. Supplied in packs of 2

Aerator, hand spray	A22D75	£15.13
Aerator, eye wash	A22LY75	£15.13
Protective caps	91AA75	£6.89

